



CITY OF DUBLIN

Community Development Department
Building & Safety Division

100 Civic Plaza, Dublin, CA 94568 • Ph: (925) 833-6620 • www.dublin.ca.gov

VOC Compliance Certification

Address: \_\_\_\_\_

Permit No.: \_\_\_\_\_

Table with 4 columns: ADHESIVE (NONE □), MANUFACTURER, CALGreen Limit 1, ACTUAL VOCs

Table with 4 columns: SEALANT (NONE □), MANUFACTURER, CALGreen Limit 1, ACTUAL VOCs

Table with 4 columns: ARCHITECTURAL COATINGS (NONE □), MANUFACTURER, CALGreen Limit 1, ACTUAL VOCs

Table with 4 columns: RESILIENT FLOORING (NONE □), MANUFACTURER, CALGreen Limit 1, ACTUAL VOCs

FORMALDEHYDE COMPLIANCE CERTIFICATION

Table with 4 columns: PRODUCT (NONE □), MANUFACTURER, CURRENT LIMIT, ACTUAL. Rows include Hardwood plywood veneer core, Hardwood plywood composite core, Particleboard, Medium density fiberboard, Thin medium density fiberboard 2.

1 See other side of page for VOC limits

2 Thin medium density fiberboard has a maximum thickness of 5/16 inch

All **carpet** installed in the building interior meets the testing and product requirements of the following: (check one)

- Carpet and Rug Institute’s Green Label
- California Department of Public Health “Standard Method for the Testing of VOCs”
- NSF/ANSI 140 at the Gold level
- Scientific Certifications Systems Indoor Advantage™ Gold
- No carpet installed on this project

I certify that the information provided on this form is accurate and that the materials used on this project comply with Section 4.504 (Residential) or 5.504 (Non-Residential) of the 2013 California Green Building Standards Code.

Print Name

Signature

Date

**TABLE 4.504.1  
ADHESIVE VOC LIMIT<sup>1,2</sup>  
Less Water and Less Exempt Compounds in Grams per Liter**

ARCHITECTURAL APPLICATIONS	CURRENT VOC LIMIT
Indoor carpet adhesives	50
Carpet pad adhesives	50
Outdoor carpet adhesives	150
Wood flooring adhesive	100
Rubber floor adhesives	60
Subfloor adhesives	50
Ceramic tile adhesives	65
VCT and asphalt tile adhesives	50
Drywall and panel adhesives	50
Cove base adhesives	50
Multipurpose construction adhesives	70
Structural glazing adhesives	100
Single-ply roof membrane adhesives	250
Other adhesives not specifically listed	50
<b>SPECIALTY APPLICATIONS</b>	
PVC welding	510
CPVC welding	490
ABS welding	325
Plastic cement welding	250
Adhesive primer for plastic	550
Contact adhesive	80
Special purpose contact adhesive	250
Structural wood member adhesive	140
Top and trim adhesive	250
<b>SUBSTRATE SPECIFIC APPLICATIONS</b>	
Metal to metal	30
Plastic foams	50
Porous material (except wood)	50
Wood	30
Fiberglass	80

1. If an adhesive is used to bond dissimilar substrates together, the adhesive with the highest VOC content shall be allowed.
2. For additional information regarding methods to measure the VOC content specified in this table, see South Coast Air Quality Management District Rule 1168.

**TABLE 4.504.2  
SEALANT VOC LIMIT  
Less Water and Less Exempt Compounds in Grams per Liter**

SEALANTS	CURRENT VOC LIMIT
Architectural	250
Marine deck	760
Nonmembrane roof	300
Roadway	250
Single-ply roof membrane	450
Other	420
<b>SEALANT PRIMERS</b>	
Architectural	
Nonporous	250
Porous	775
Modified bituminous	500
Marine deck	760
Other	750

**TABLE 4.504.3  
VOC CONTENT LIMITS FOR ARCHITECTURAL COATINGS<sup>2,3</sup>  
Grams of VOC per Liter of Coating,  
Less Water and Less Exempt Compounds**

COATING CATEGORY	EFFECTIVE 1/1/2010	EFFECTIVE 1/1/2012
Flat coatings	50	
Nonflat coatings	100	
Nonflat-high gloss coatings	150	
<b>SPECIALTY COATINGS</b>		
Aluminum roof coatings	400	
Basement specialty coatings	400	
Bituminous roof coatings	50	
Bituminous roof primers	350	
Bond breakers	350	
Concrete curing compounds	350	
Concrete/masonry sealers	100	
Driveway sealers	50	
Dry fog coatings	150	
Faux finishing coatings	350	
Fire resistive coatings	350	
Floor coatings	100	
Form-release compounds	250	
Graphic arts coatings (sign paints)	500	
High temperature coatings	420	
Industrial maintenance coatings	250	
Low solids coatings <sup>1</sup>	120	
Magnesite cement coatings	450	
Mastic texture coatings	100	
Metallic pigmented coatings	500	
Multicolor coatings	250	
Pretreatment wash primers	420	
Primers, sealers, and undercoaters	100	
Reactive penetrating sealers	350	
Recycled coatings	250	
Roof coatings	50	
Rust preventative coatings	400	250
Shellacs		
Clear	730	
Opaque	550	
Specialty primers, sealers and undercoaters	350	100
Stains	250	
Stone consolidants	450	
Swimming pool coatings	340	
Traffic marking coatings	100	
Tub and tile refinish coatings	420	
Waterproofing membranes	250	
Wood coatings	275	
Wood preservatives	350	
Zinc-rich primers	340	

1. Grams of VOC per liter of coating, including water and including exempt compounds.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the table.
3. Values in this table are derived from those specified by the California Air Resources Board, Architectural Coatings Suggested Control Measure, February 1, 2008. More information is available from the Air Resources Board.